



Pushing Performance  
Since 1945

# Han-Fast Lock 4-6mm², Ag



Part number	09 08 000 7923
Specification	Han-Fast Lock 4-6mm², Ag

## Identification

Category	Contacts
Series	Han-Fast® Lock
Type of contact	PCB contact
Description of the contact	Without pin

## Version

Pack contents	Single contact
---------------	----------------

## Technical characteristics

Conductor cross-section	4 ... 6 mm²
Rated current	≤60 A
Contact resistance	≤2 mΩ
Stripping length	7.5 mm

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (locking)	Copper alloy
Surface (locking)	Passivated
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances Not contained

California Proposition 65 substances Yes

## Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076  
CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	1
Net weight	1.22 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140014893
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)